

Compact Fans - All Metal



AC Axial

Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (mA)	Speed (RPM)	Power (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)	Wt. kg
120 x 120 x 38 mm - Metal (Pack size: 20 No's)										
12A230HBAC-M	Ball	230	50/60	100/90	2700/3100	17/15	95/107	8.4/9.4	42/46	12
172 x 150 x 55 mm - Metal (Pack size: 10 No's)										
17A230HBAC-M	Ball	230	50/60	250/230	2800/3250	42/42	195/230	14/16	49/53	12
225 x 225 x 80 mm - Metal (Pack size: 8 No's)										
225A230HBAC-M	Ball	230	50/60	300/325	2500/2800	65/70	530/600	17/14	59/61	20
225A230HBAC-M-J	Ball	230	50	420	2750	82	600	18.7	60	20
280 x 280 x 80 mm - Metal (Pack size: 6 No's)										
280A230HBAC-M	Ball	230	50/60	590/820	2500/2700	119/130	1090/1130	16.5/20	68/70	21

Also available 115VAC & 415VAC

DC Brushless

Model	Bearing	Voltage (VDC)	Current (mA)	Speed (RPM)	Power (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)	Wt. kg
225 x 225 x 80 mm - Metal (Pack size: 6 No's)									
225A48HBDC - M	Ball	48	1100	2850	52.8	647	25	67	20
280 x 280 x 80 mm - Metal (Pack size: 6 No's)									
280A48HBDC - M	Ball	48	1900	2700	91.2	1130	22	69	21

Note:

■ Weight mentioned is for the pack size.

Specifications subject to change without notice